



# TEXACO CANOPUS<sup>®</sup>

## 13, 19, 68

---

### CUSTOMER BENEFITS

Texaco Canopus oils deliver value through:

- **High resistance to forming emulsions** due to excellent water separating characteristics.
- **Long lubricant life** provided by outstanding stability.
- **Good lubricant compatibility** — Compatible with other mineral-based and polyalphaolefin lubricants.

### FEATURES

Texaco Canopus oils are high quality, high viscosity index un compounded oils with excellent water separating characteristics.

Texaco Canopus oils possess good natural thermal and oxidation stability. Their high viscosity index makes them suitable for use over a wide temperature range. In a circulating oil system, compressor, or lightly loaded gear case, they will maintain a high film strength, protecting metal parts. Lubricant-related deposits will be kept to a minimum due to the excellent stability of these oils. System contaminants such as dirt and moisture can be easily removed from these oils by proper filtration.

Texaco Canopus **68** is registered with NSF and is acceptable as a lubricant where there is no possibility of food contact (H2) in and around food processing areas. The NSF Nonfood Compounds Registration Program is a continuation of the USDA product approval and listing program, which is based on meeting regulatory requirements of appropriate use, ingredient review and labeling verification.

### APPLICATIONS

Texaco Canopus oils are recommended for use in many circulating oil systems, as cylinder lubricants in double-acting reciprocating compressors, and for the lubrication of both cylinders and running gears of single-acting compressors.

Because of their compatibility, Texaco Canopus oils are good for flushing lubricant systems as well.

Texaco Canopus oils can be used for hand oiling. Their high viscosity index makes them suitable for use over a wide temperature range.

Do not use Texaco Canopus 13, 19, or 68 in high pressure systems in the vicinity of flames, sparks and hot surfaces. Use only in well ventilated areas. Keep container closed.

## TYPICAL TEST DATA

	<b>13</b>	<b>19</b>	<b>68</b>
<i>Product Number</i>	220519	220522	220659
<i>MSDS Number</i>	8697	8649	8649
API Gravity	34.0	34.4	31.3
Viscosity, Kinematic cSt at 40°C cSt at 100°C	12.1 2.9	19.7 4.0	64.6 8.4
Viscosity, Saybolt SUS at 100°F SUS at 210°F	70 36.1	104 39.7	335 54.5
Viscosity Index	80	98	99
Flash Point, °C(°F)	179(354)	213(415)	242(468)
Fire Point, °C(°F)	204(399)	236(457)	276(529)
Pour Point, °C(°F)	-40(-40)	-12(+10)	-15(+5)

Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing.