



TEXACO CHAIN, BAR AND SPROCKET LUBRICANT

CUSTOMER BENEFITS

Texaco Chain, Bar and Sprocket Lubricant delivers value through:

- **Reduced wear** — Minimize wear for the chain, bar, and sprocket.
- **Tackiness** — The increased tackiness additive keeps the oil on the chain and prevents sling-off when the chain is traveling at high speeds resulting in less waste and reduced consumption.
- **Field experience** — Used extensively in the field with proven experience.

FEATURES

Texaco Chain, Bar and Sprocket Lubricant is a very tacky, tough, lubricant made from special high viscosity base oils.

Texaco Chain, Bar and Sprocket Lubricant is manufactured to meet the needs of the forest products industry under the most adverse operating conditions.

To a logger, chainsaw lubrication is one of the most demanding requirements for efficient chainsaw performance and operation. Texaco Chain, Bar and Sprocket Lubricant was designed to meet this demand with economy in mind.

Texaco Chain, Bar and Sprocket Lubricant is ideal for cool weather conditions of 0-15°C (32°-60°F) to assure a proper flow from either hand operated or automatic chain oilers.

APPLICATIONS

Texaco Chain, Bar and Sprocket Lubricant is recommended for use in all types of chain saws using either hand-operated or automatic chain oilers to lubricate the chain, bar, and sprocket.

Other possible uses include chain drives on straddle lift lumber carriers and motorcycle chains, as well as lawnmowers and farm equipment.

TYPICAL TEST DATA

<i>Product Number</i>	221521
<i>MSDS Number</i>	8646
API Gravity	27.9
Viscosity, Kinematic cSt at 40°C	95
Viscosity, Saybolt SUS at 100°F	495
Flash Point, °C(°F)	218(424)
Pour Point, °C(°F)	-27(-17)

Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing