



TEXACO GEOTEX[®] FLEET

SAE 15W-40

CUSTOMER BENEFITS

Texaco Geotex Fleet delivers value through:

- **Alternative fuel performance** — Recommended for medium and heavy duty vehicles powered by natural gas and propane-fueled engines where engine manufacturers recommend a low ash lubricant with improved valve train wear performance.
- **Low wear** — Provide excellent protection against piston, ring, and liner scuffing, scoring, and wear, including wear protection for slider follower valve trains in alternative fuel engines.
- **Clean crankcases and top decks** — Minimize the formation of sludge in the crankcase and in the valve rocker cover/top deck area.
- **Reduced valve recession** — The level and type of ash producing additives in the oils provide minimum valve recession with low levels of combustion chamber deposits to minimize the potential for pre-ignition and spark plug fouling.
- **Excellent piston and ring belt deposit control** — An optimized blend of detergents, dispersants, and inhibitors provide excellent deposit control throughout the entire engine.

FEATURES

Texaco Geotex Fleet is a premium quality heavy duty multigrade gas engine oil for use in engines running on compressed natural gas (CNG), liquified natural gas (LNG), and liquified petroleum gas (LPG).

It is formulated with Group II base stocks and a premium low ash additive package specially formulated for advanced lean burn, spark ignited, natural gas engines equipped with either roller or slider followers.

Texaco Geotex Fleet provides outstanding oxidation and nitration resistance, which reduce the buildup of insolubles and provide extended oil and filter life.

In vehicular and stationary four-stroke engines, Texaco Geotex Fleet:

- minimizes valve recession
- provides easier engine startup and better oil flow in low temperature conditions
- reduces oil consumption

APPLICATIONS

Texaco Geotex Fleet is recommended for these alternative fuel engines:

- **Cummins** B5.9G, C8.3G
- **Detroit Diesel**¹ Series 50G, 60G

Texaco Geotex Fleet meets the performance requirements of:

- **Cummins** CES 20074 (B5.9G and C8.3G only)
- **Detroit Diesel** 7SE272-9510 (Series 50G and 60G only)

Texaco Geotex Fleet is recommended for use in selected alternative fuel vehicles - metropolitan transit vehicles and local delivery trucks operating on compressed natural gas (CNG), liquified petroleum gas (LPG), or liquified natural gas (LNG).

TYPICAL TEST DATA

SAE Grade	15W-40
CPS Number	222028
MSDS Number	13158
API Gravity	30.1
Viscosity, Kinematic cSt at 40°C cSt at 100°C	115 15
Viscosity Index	136
Viscosity, Cold Crank, C/Poise	-15/31.5
Flash Point, °C(°F)	230(446)
Pour Point, °C(°F)	-36(-33)
Sulfated Ash, wt %	0.55
Acid Number, ASTM D 664	1.0
Base Number, ASTM D 2896	5.1
Phosphorus, ppm	700
Zinc, ppm	780

Typical test data are average values only. Minor variations which do not affect performance are to be expected in normal manufacturing.

1. Detroit Diesel is a registered trademark of Detroit Diesel Corporation.