



HAVOLINE[®] AUTOMATIC TRANSMISSION FLUID DEXRON[®]-VI

CUSTOMER BENEFITS

Havoline Automatic Transmission Fluid DEXRON[®]-VI delivers value through:

- **Warranty coverage** as an officially approved General Motors fluid
- **Improved durability of viscosity and frictional properties** to ensure smooth operation in General Motors transmissions
- **Extended drain intervals** of at least 100,000 miles under normal operating conditions
- **Back serviceability** to cover all earlier DEXRON recommendations

FEATURES

Havoline Automatic Transmission Fluid DEXRON[®]-VI is formulated with high purity synthetic base stocks. It is designed to maintain its viscosity through excellent oxidation stability and use of long lasting viscosity modifiers. Internal General Motors tests have shown more than twice the durability and stability in friction tests compared to standard DEXRON-III fluids. This will ensure consistent and smooth shift performance, even under extreme driving conditions. Extensive validation testing by General Motors has shown DEXRON-VI to be significantly better than previous DEXRON fluids in nearly every performance area.

Havoline Automatic Transmission Fluid DEXRON[®]-VI:

- Maintains friction control for smooth, consistent shifting
- Prevents clutch shudder in torque converters
- Improves fuel economy relative to previous DEXRON fluids because of lower viscous drag and outstanding low temperature pumpability
- Practically eliminates transmission overhauls due to sludge, corrosion, and wear
- Operates well over a wide temperature range
- Resists thermal and oxidative breakdown
- Provides sufficient viscosity at high temperatures with minimal sheardown
- Protects gears, bearings, clutch plates, seals, bushings and other components from wear and degradation
- Resists foaming and thereby gives better operability and longer equipment life

APPLICATIONS

Havoline Automatic Transmission Fluid DEXRON[®]-VI is designed specifically for use in all General Motors HydraMatic transmissions produced for Model Year 2006 and beyond. It is the latest generation technology approved for use by General Motors in automatic transmissions and automatic transaxles where a DEXRON[®]-VI fluid is specified. It is also back serviceable in transmissions calling for DEXRON[®]-III or DEXRON[®]-II fluids.¹

Havoline Automatic Transmission Fluid DEXRON[®]-VI is not recommended for use in transmissions which do not specify a DEXRON[®] fluid. In particular, it should not be used in applications which call for Allison C-4, ATF+3[®], ATF+4[®], or MERCON[®] type fluids.²

Havoline Automatic Transmission Fluid DEXRON[®]-VI meets General Motors specification GMN10060 and has been registered with license number J60308.

Do not use in high pressure systems in the vicinity of flames, sparks and hot surfaces. Use only in well ventilated areas. Keep container closed.

TYPICAL TEST DATA

<i>Product Number</i>	222269
<i>MSDS Number</i>	16358
API Gravity	35.8
Viscosity, Kinematic cSt at 40°C cSt at 100°C	29.8 6.0
Viscosity, Brookfield cP at -40°C	12,030
Viscosity Index	151
Flash Point, °C(°F)	206(403)
Pour Point, °C(°F)	-54(-65)
Color	Red

Typical test data are average values only. Minor variations which do not affect performance are to be expected in normal manufacturing.

1. DEXRON is a registered trademark of General Motors Corporation.
2. MERCON is a registered trademark of Ford Motor Company. ATF+3 and ATF+4 are registered trademarks of Chrysler Corporation