



TEXACO TEXGLASS MV

CUSTOMER BENEFITS

Texaco Texglass MV delivers value through:

- **Ability to maintain film thickness** — High viscosity index indicates an oil that maintains film thickness at high temperatures
- **Sludge protection** — Detergents and dispersants minimize deposits on metal surfaces
- **Rust protection** — Contains a rust inhibitor to protect metal surfaces
- **Long lubricant life** — Resists thermal oxidation and viscosity increase, providing long lubricant life.
- **Foam inhibition**

FEATURES

Texaco Texglass MV is a machine oil designed for use in the glass manufacturing process.

It is manufactured from highly refined mineral base oils and contains an additive package with antiwear, dispersant and detergent properties.

It has a high viscosity index to assure good film strength between metal surfaces under moderate loads and temperatures. This film strength is further enhanced by the antiwear additive protection.

The foam and aeration suppressant allows the quick release of entrained air, also improving film strength.

APPLICATIONS

Texaco Texglass MV is recommended as a machine oil and constant cushion oil for I.S. glass machines. It is also designed for use in linkage and gearboxes, central lubrication systems, mechanical gob distributors, blow-head and funnel cams.

TYPICAL TEST DATA

<i>CPS Number</i>	222628
<i>MSDS Number</i>	8911
API Gravity	29.8
Viscosity, Kinematic cSt at 40°C cSt at 100°C	111 14.5
Viscosity, Saybolt SUS at 100°F SUS at 210°F	572 77.5
Viscosity Index	134
Flash Point, °C(°F)	234(453)
Pour Point, °C(°F)	-38(-36)
Foaming Tendency, Sequence II, 0 min, mL	15

Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing.